

FMOG FLOW METERS

LUBES & DEF

PERFORMANCE MEETS ACCURACY IN THE FMOG LINE OF METERS

FMOG FOR HEAVY LUBES

TECHNICAL SPECIFICATIONS & FEATURES

Used with high viscosity oils

Flow:	2.6 gpm
Accuracy:	0.5%
Inlet/outlet:	0.5" NPT
Max. pressure:	10 bar

PART

DESCRIPTION

US027176401	FMOG ALUMINUM HEAVY DUTY OIL
-------------	------------------------------




FMOG FOR DEF

TECHNICAL SPECIFICATIONS & FEATURES

Used with Diesel Exhaust Fluid (DEF)

Lithium battery with 10-year battery life

LCD display

Inlet/outlet: 1" BSP

Pulse ratio: 100:1 single channel

PART

DESCRIPTION

US253400030	FMOG DEF PULSER
-------------	-----------------




HAND FLOW METERS/NOZZLES

TECHNICAL SPECIFICATIONS & FEATURES

Track total gallons

Non-resettable totalizer

Oval meter | Aluminum housing

Lithium battery with 10-year battery life

Flow (max.): 4 gpm

PART

DESCRIPTION

US027170211	FMOG HAND FLOW METER
1781501	LUBE NOZZLE W/ DISPLAY
02724032	LUBE NOZZLE - NO DISPLAY


